


STA45SLM

Ø45mm Slim LED Tower Light



STA45SLM series



Customization

- Wall mount bracket options : Used for mounting on the vertical surface



Wall Mount Bracket
STAWB45



Common Specifications(STA45SLM/ STA45SLMP)

- Ø45mm direct mount/pole mount tower lights
- Aluminum housing displays a unique metallic luster that defines a high class product
- Excellent visibility by using a high brightness LED with a special diffusion lens
- Lens maintains a semi-transparent color when not emitting the specific color of the signal under operation
- Steady mode only(can operate flashing mode with external control) with fixed user selected color arrangement
- Easy mounting with the bolts/screws located at the bottom of the product
- Built-in buzzer available (Volume : Max 90dB at 1m)
- Materials : Lens-Acrylic, Filter lens -AS, Housing-AI
- Ambient operating temperature : -30°C to +50°C
- Protection rating : Standard type-IP44, Built-in buzzer type-IP23
- Certificates : CE Compliant, UL Listed



STA45SLM Ø45mm Direct Mount, LED Steady

Model number	Layer	Voltage	Current	Certificates	Weight	Color
STA45SLM Steady STA45SLM-BZ Steady w/ built-in buzzer	1	AC/DC12V AC/DC24V	0.100A 0.050A	CE UL	0.50kg	• R-Red
	2	AC/DC12V AC/DC24V	0.200A 0.100A		0.54kg	• R-Red • G-Green
	3	AC/DC12V AC/DC24V	0.300A 0.150A		0.58kg	• R-Red • A-Amber • G-Green
	4	AC/DC12V AC/DC24V	0.400A 0.200A		0.63kg	• R-Red • A-Amber • G-Green • B-Blue
	5	AC/DC12V AC/DC24V	0.500A 0.250A		0.68kg	• R-Red • A-Amber • G-Green • B-Blue • W-White

Signal/ Audible Line Current(per each layer)

Voltage settings	DC12V	DC24V
Signal line current	0.100A	0.050A
Audible line current	0.016A	0.031A



Technical Diagram

(Units : mm)

